TrafFix Vertical Panel Barricades

Featuring Step-n-Lock™ Panel Design with Recycled Rubber Base





TrafFix Devices Inc.



New Traffix Vertical Panel Barricade

Tested and certified to meet the crashworthy requirements of NCHRP-350 and M.U.T.C.D. standards



36" x 8" TrafFix Vertical Panel Barricade with 28lb. recycled rubber base 34000 Series



24" x 12" TrafFix Vertical Panel Barricade with light and 43lb. recycled rubber base 33000 Series



24" x 8" TrafFix Vertical Panel Barricade with light and 43lb. recycled rubber base 34000 Series



29 1/2" x 12" Traffix Vertical Panel Barricade with 28lb. recycled rubber base 33000 Series

Traffix Vertical Panel Barricades consist of durable blow molded polyethylene panels and recycled rubber bases.

To assemble, simply "Step-n-Lock" the vertical panel into the base. No heavy rings or bases that must be lifted over the top of the panel.

For transportation and storage, both the panels and bases can be easily separated and stacked.

The panel separates from the base when impacted by a vehicle.


The panel face is recessed to minimize abrasions and scratches to the expensive reflective sheeting. If severly damaged, the reflective sheeting can be replaced.

The bases are made from recycled rubber and weigh either 28 or 43lbs.



Messages and Legends

A wide variety of messages and legends can be printed on one or two sides of the panel. Engineer, high performance or diamond grade reflective sheeting is available. Ideal for parking lots, schools, churches, or in-plant applications.



Step-n-Lock Panel

Six locking buttons are molded into the panel and correspond to six matching recesses molded in the base. Simply step down on the foot hole to lock the panel in place. The Step-n-Lock design ensures the panel will remain vertically locked in place and "square to traffic." Panel sizes, messages and legends can be intermixed with either the 28 or 43lb, base.





Rubber Base

Made from 100% recycled rubber, the base incorporates two easy-grip carrying handles. A vulcanized rubber center section provides reinforcement from wear and tear due to panel separation. On the under side of the base, there are four raised anti-rotational foot pads to minimize movement from wind, or turbulence from passing vehicles.

Copyright February, 2001 Traffix Devices, Inc. Step-n-Lock is a trademark of Traffix Devices, Inc. Traffix is a registered trademark of Traffix Devices, Inc. U.S. patents pending.





Distributed by:

220 Calle Pintoresco, San Clemente, CA 92672 (949) 361-5663 FAX (949) 361-9205 www.traffixdevices.com